

Brilliant i-2330 SXGA Document Camera Specifications

Model No.	i-2330
Sensor	1/3" CMOS
Total pixel	3 Megapixel
Zoom	9x optical, 12x digital
Frame rate	24
Shooting area	Max: 13.5" x 10.6" /34.3cm x 26.9cm Min: 0.1" x 0.1"/0.3cm x 0.3cm
Focus	Auto/manual
Native output signal	SXGA(1280x1024)
Converted output signal	WXGA, XGA
Resolution (Horizontal)	≥ 750 TV lines
White balance	Auto/manual
Color adjustment	Yes
Brightness adjustment	Yes
Image capture	Yes, 1,000 NON-volatile images
Video recording	Yes, with sound
Image mirror	Yes
Image rotation	90, 180, 270 (frozen)
Image split	Yes
Image freeze	Yes
Picture in picture	Yes
Title freeze	Yes
Text mode	Yes
Black/white/color conversion	Yes
Positive/negative conversion	Yes
OSD	Yes
Built-in video scaler	Yes
INPUT TERMINALS	
VGA	x2
VIDEO	x1
S-VIDEO	x1
AUDIO	x4
MICROPHONE	x1
OUTPUT TERMINALS	



DVI	x1
VGA	x2
VIDEO	x1
AUDIO	x1
S-VIDEO	x1
OTHER TERMINALS	
USB2.0	Host×1(Mouse, Memory stick) Slave×1(USB camera/Build-in image download)
USB driver and software	Windows 2000/XP/Vista, Mac OS10.4 or above. Driver plug and play
RS232 (computer controllable)	x1
Remote control	
	Yes(360°controllable)
Kensington lock	
	Yes
Built-in LCD screen	
	Yes
Light source	
	Top arm light×1 (LED) A4 size lightbox (LED)
Operating temperature	
	32°F to 104°F 0°C to 40°C
Dimensions	
	Folded: 19.48" x 14.56" x 5" 49.5cm x 37cm x 12.8cm Setup: 21.25" × 14.56" × 21.25" 54cm x 37cm x 54cm
Power supply	
	12V DC power adapter
Weight(net)	
	11 lbs/ 5 kg

Design and specifications are subject to change without notice.